

EProClock® GENERATOR FOR INTEL® CK505 COMPLIANCE

Features

- Compliant Intel CK505 Clock spec
- Low power push-pull type differential output buffers
- Integrated resistors on differential clocks
- Wireless friendly 3-bits slew rate control on single-ended clocks
- Differential CPU clocks with pin selectable frequency
- 100 MHz Differential SRC clocks
- Selectable Differential SATA or SRC clocks
- 96 MHz Differential DOT clock
- 48 MHz USB clock
- Selectable 12 or 48 MHz clock
- 25 MHz output
- Buffered Reference Clock 14.318 MHz
- 14.318 MHz Crystal Input or Clock input
- I²C support with readback capabilities
- Triangular Spread Spectrum profile for maximum electromagnetic interference (EMI) reduction
- Industrial Temperature: -40 to 85 °C
- 3.3 V power supply
- 56-pin QFN package

Selectable Differential SRC or CPU Clock



| CPU | SRC | SATA | DOT96 | 48M | 48M/12M | 33M | 25M | 14.318M |
|-------|-------|-------|-------|------|---------|-----|-----|---------|
| x2/x3 | x4/x7 | x0/x1 | x1 | x1/2 | x1 | x2 | x1 | x1 |

EProClock® Programmable Technology

- > 4000 bits of configurations
- Can be configured through SMBus or hard coded
- Custom frequency sets
- Differential skew control on true or compliment or both
- Differential duty cycle control on true or compliment or both
- Differential amplitude control
- Differential and single-ended slew rate control
- Program Internal or External series resistor on single-ended clocks
- Program different spread profiles
- Program different spread modulation rate

Selectable Differential SRC or CPU Clock

| CPU | SRC | SATA | DOT96 | 48M | 48M/12M | 33M | 25M | 14.318M |
|-------|-------|-------|-------|------|---------|-----|-----|---------|
| x2/x3 | x4/x7 | x0/x1 | x1 | x1/2 | x1 | x2 | x1 | x1 |



Patents pending

SL28EB742

Description

The SL28EB742 is a high-performance clock generator supporting Intel Cedarview platforms. The SL28EB742 is rated to support extended grade temperature. Utilizing an inexpensive 14.318 MHz crystal, it is capable of supporting multiple frequencies from four PLLs. The CPU clock can support a frequency range from 83.33 to 166 MHz by configuration of two strap pins. With a combination of strap pins and an I²C interface, the device allows maximum configurability.

EProClock[®] is the world's first non-volatile programmable clock. The EProClock[®] technology allows board designer to promptly achieve optimum compliance and clock signal integrity; historically, attainable typically through device and/or board redesigns. EProClock[®] technology can be configured through SMBus or hard coded.

Functional Block Diagram




TABLE OF CONTENTS

| <u>Section</u> | <u>Page</u> |
|---|--------------------|
| 1. Electrical Specifications | 4 |
| 2. Functional Description | 11 |
| 2.1. Powerdown (<u>PD#</u>) Clarification | 11 |
| 2.2. Powerdown (<u>PD#</u>) Assertion | 11 |
| 2.3. Powerdown (<u>PD#</u>) Deassertion | 12 |
| 2.4. <u>CPU_STP#</u> Assertion | 14 |
| 2.5. <u>CPU_STP#</u> Deassertion | 14 |
| 2.6. <u>PCI/SRC_STP#</u> Assertion | 15 |
| 2.7. <u>PCI/SRC_STP#</u> Deassertion | 15 |
| 3. Test and Measurement Setup | 16 |
| 3.1. Single-ended Clocks | 16 |
| 3.2. Differential Clock Signals | 17 |
| 4. Control Registers | 19 |
| 4.1. Frequency Select Pin FS | 19 |
| 4.2. Serial Data Interface | 20 |
| 4.3. Data Protocol | 20 |
| 5. Pin Descriptions: 56-Pin QFN | 35 |
| 6. Ordering Guide | 39 |
| 7. Package Outline | 40 |
| Document Change List | 42 |
| Contact Information | 43 |

1. Electrical Specifications

Table 1. Recommended Operating Conditions

(VDD = 3.3 V, TA = 25 °C)

| Parameter | Symbol | Test Condition | Min | Typ | Max | Unit |
|-----------------------------|-----------------------------|----------------|------|-----|------|------|
| Supply Voltage (extended) | VDD _(industrial) | 3.3 V ±5% | 3.13 | 3.3 | 3.46 | V |
| Supply Voltage (commercial) | VDD _(commercial) | 3.3 V ±10% | 2.97 | 3.3 | 3.63 | V |

Table 2. DC Electrical Specifications

| Parameter | Symbol | Test Condition | Min | Max | Unit |
|--------------------------------|--------------------|--|-----------------------|-----------------------|------|
| 3.3 V Operating Voltage | VDD core | 3.3 ± 5% | 3.135 | 3.465 | V |
| 3.3 V Input High Voltage (SE) | V _{IH} | | 2.0 | V _{DD} + 0.3 | V |
| 3.3 V Input Low Voltage (SE) | V _{IL} | | V _{SS} - 0.3 | 0.8 | V |
| Input High Voltage | V _{IHI2C} | SDATA, SCLK | 2.2 | — | V |
| Input Low Voltage | V _{ILI2C} | SDATA, SCLK | — | 1.0 | V |
| FS Input High Voltage | V _{IH_FS} | | 0.7 | VDD+0.3 | V |
| FS Input Low Voltage | V _{IL_FS} | | V _{SS} - 0.3 | 0.35 | V |
| Input High Leakage Current | I _{IH} | Except internal pull-down resistors, 0 < V _{IN} < V _{DD} | — | 5 | µA |
| Input Low Leakage Current | I _{IL} | Except internal pull-up resistors, 0 < V _{IN} < V _{DD} | -5 | — | µA |
| 3.3 V Output High Voltage (SE) | V _{OH} | I _{OH} = -1 mA | 2.4 | — | V |
| 3.3 V Output Low Voltage (SE) | V _{OL} | I _{OL} = 1 mA | — | 0.4 | V |
| High-impedance Output Current | I _{OZ} | | -10 | 10 | µA |
| Input Pin Capacitance | C _{IN} | | 1.5 | 5 | pF |
| Output Pin Capacitance | C _{OUT} | | | 6 | pF |
| Pin Inductance | L _{IN} | | — | 7 | nH |
| Power Down Current | IDD_PD | | — | 1 | mA |
| Dynamic Supply Current | IDD_3.3 V | All outputs enabled. SE clocks with 5" traces. Differential clocks with 5" traces. Loading per CK505 spec. | — | 115 | mA |

Table 3. AC Electrical Specifications

| Parameter | Symbol | Test Condition | Min | Max | Unit |
|------------------------------------|-------------------|--|---------------|----------|------|
| Long-term Accuracy | L_{ACC} | Measured at VDD/2 differential | — | 250 | ppm |
| Clock Input | | | | | |
| CLKIN Duty Cycle | T_{DC} | Measured at VDD/2 | 47 | 53 | % |
| CLKIN Rise and Fall Times | T_R/T_F | Measured between 0.2 V _{DD} and 0.8 V _{DD} | 0.5 | 4.0 | V/ns |
| CLKIN Cycle to Cycle Jitter | T_{CCJ} | Measured at VDD/2 | — | 250 | ps |
| CLKIN Long Term Jitter | T_{LTJ} | Measured at VDD/2 | — | 350 | ps |
| Input High Voltage | V_{IH} | XIN / CLKIN pin | 2 | VDD+0.3 | V |
| Input Low Voltage | V_{IL} | XIN / CLKIN pin | — | 0.8 | V |
| Input High Current | I_{IH} | XIN / CLKIN pin, V _{IN} = VDD | — | 35 | μA |
| Input Low Current | I_{IL} | XIN / CLKIN pin, 0 < V _{IN} < 0.8 | -35 | — | μA |
| CPU at 0.7 V | | | | | |
| CPU Duty Cycle | T_{DC} | Measured at 0 V differential | 45 | 55 | % |
| 83.33 MHz CPU Period | T_{PERIOD} | Measured at 0 V differential at 0.1s | 11.99880 | 12.00120 | ns |
| 83.33 MHz CPU Period, SSC | $T_{PERIODSS}$ | Measured at 0 V differential at 0.1s | 12.02887 2 | 12.03128 | ns |
| 83.33 MHz CPU Absolute Period | $T_{PERIODAbs}$ | Measured at 0 V differential at 1 clock | 11.18969 | 12.16344 | ns |
| 83.33 MHz CPU Absolute Period, SSC | $T_{PERIODSSAbs}$ | Measured at 0 V differential at 1 clock | 11.89687 | 12.16344 | ns |
| 100 MHz CPU Period | T_{PERIOD} | Measured at 0 V differential at 0.1s | 9.99900 | 10.0010 | ns |
| 100 MHz CPU Period, SSC | $T_{PERIODSS}$ | Measured at 0 V differential at 0.1s | 10.02406 | 10.02607 | ns |
| 100 MHz CPU Absolute Period | $T_{PERIODAbs}$ | Measured at 0 V differential at 1 clock | 9.87400 | 10.1260 | ns |
| 100 MHz CPU Absolute Period, SSC | $T_{PERIODSSAbs}$ | Measured at 0 V differential at 1 clock | 9.87406 | 10.1762 | ns |
| 133 MHz CPU Period | T_{PERIOD} | Measured at 0 V differential at 0.1s | 7.49925 | 7.50075 | ns |
| 133 MHz CPU Period, SSC | $T_{PERIODSS}$ | Measured at 0 V differential at 0.1s | 7.51804 | 7.51955 | ns |
| 133 MHz CPU Absolute Period | $T_{PERIODAbs}$ | Measured at 0 V differential at 1 clock | 7.41425 | 7.58575 | ns |
| 133 MHz CPU Absolute period, SSC | $T_{PERIODSSAbs}$ | Measured at 0 V differential at 1 clock | 7.41430 | 7.62340 | ns |

Table 3. AC Electrical Specifications (Continued)

| Parameter | Symbol | Test Condition | Min | Max | Unit |
|--|---------------------------|---|----------|----------|------|
| 166 MHz CPU Period | T_{PERIOD} | Measured at 0 V differential at 0.1s | 5.99940 | 6.00060 | ns |
| 166 MHz CPU Period, SSC | $T_{PERIODSS}$ | Measured at 0 V differential at 0.1s | 6.01444 | 6.01564 | ns |
| 166 MHz CPU Absolute period | $T_{PERIODAbs}$ | Measured at 0 V differential at 1 clock | 5.91440 | 6.08560 | ns |
| 166 MHz CPU Absolute period, SSC | $T_{PERIODSSAbs}$ | Measured at 0 V differential at 1 clock | 5.91444 | 6.11572 | ns |
| CPU Cycle to Cycle Jitter | T_{CCJ} | Measured at 0 V differential | — | 85 | ps |
| CPU Cycle to Cycle Jitter for CPU 2 | $T_{CCJ} (CPU2)$ | Measured at 0 V differential | — | 125 | ps |
| CPU0 to CPU1 skew | Skew | Measured at 0 V differential | — | 100 | ps |
| Long-term Accuracy | L_{ACC} | Measured at 0 V differential | — | 100 | ppm |
| CPU Rising/Falling Slew rate | T_R / T_F | Measured differentially from ± 150 mV | 2.5 | 8 | V/ns |
| Rise/Fall Matching | T_{RFM} | Measured single-endedly from ± 75 mV | — | 20 | % |
| Voltage High | V_{HIGH} | | | 1.15 | V |
| Voltage Low | V_{LOW} | | -0.3 | — | V |
| Crossing Point Voltage at 0.7 V Swing | V_{OX} | | 300 | 550 | mV |
| SRC at 0.7 V | | | | | |
| SRC Duty Cycle | T_{DC} | Measured at 0 V differential | 45 | 55 | % |
| 100 MHz SRC Period | T_{PERIOD} | Measured at 0 V differential at 0.1s | 9.99900 | 10.0010 | ns |
| 100 MHz SRC Period, SSC | $T_{PERIODSS}$ | Measured at 0 V differential at 0.1s | 10.02406 | 10.02607 | ns |
| 100 MHz SRC Absolute Period | $T_{PERIODAbs}$ | Measured at 0 V differential at 1 clock | 9.87400 | 10.1260 | ns |
| 100 MHz SRC Absolute Period, SSC | $T_{PERIODSSAbs}$ | Measured at 0 V differential at 1 clock | 9.87406 | 10.1762 | ns |
| Any SRC Clock Skew from the earliest bank to the latest bank | $T_{SKEW}(\text{window})$ | Measured at 0 V differential | — | 3.0 | ns |
| SRC Cycle to Cycle Jitter | T_{CCJ} | Measured at 0 V differential | — | 85 | ps |
| SRC Long Term Accuracy | L_{ACC} | Measured at 0 V differential | — | 100 | ppm |
| SRC Rising/Falling Slew Rate | T_R / T_F | Measured differentially from ± 150 mV | 2.5 | 8 | V/ns |

Table 3. AC Electrical Specifications (Continued)

| Parameter | Symbol | Test Condition | Min | Max | Unit |
|---------------------------------------|-----------------|---|---------|---------|------|
| Rise/Fall M-atching | T_{RFM} | Measured single-endedly from ± 75 mV | — | 20 | % |
| Voltage High | V_{HIGH} | | | 1.15 | V |
| Voltage Low | V_{LOW} | | -0.3 | — | V |
| Crossing Point Voltage at 0.7 V Swing | V_{OX} | | 300 | 550 | mV |
| DOT96 at 0.7 V | | | | | |
| DOT96 Duty Cycle | T_{DC} | Measured at 0 V differential | 45 | 55 | % |
| DOT96 Period | T_{PERIOD} | Measured at 0 V differential at 0.1s | 10.4156 | 10.4177 | ns |
| DOT96 Absolute Period | $T_{PERIODAbs}$ | Measured at 0 V differential at 0.1s | 10.1656 | 10.6677 | ns |
| DOT96 Cycle to Cycle Jitter | T_{CCJ} | Measured at 0 V differential at 1 clock | — | 250 | ps |
| DOT96 Long Term Accuracy | L_{ACC} | Measured at 0V differential at 1 clock | — | 100 | ppm |
| DOT96 Rising/Falling Slew Rate | T_R / T_F | Measured differentially from ± 150 mV | 2.5 | 8 | V/ns |
| Rise/Fall Matching | T_{RFM} | Measured single-endedly from ± 75 mV | — | 20 | % |
| Voltage High | V_{HIGH} | | | 1.15 | V |
| Voltage Low | V_{LOW} | | -0.3 | — | V |
| Crossing Point Voltage at 0.7 V Swing | V_{OX} | | 300 | 550 | mV |
| SATA at 0.7 V | | | | | |
| SATAM Duty Cycle | T_{DC} | Measured at 0V differential | 45 | 55 | % |
| SATA Cycle to Cycle Jitter | T_{CCJ} | Measured at 0V differential at 1 clock | — | 125 | ps |
| SATA Long Term Accuracy | L_{ACC} | Measured at 0V differential at 1 clock | — | 100 | ppm |
| SATA Rising/Falling Slew Rate | T_R / T_F | Measured differentially from ± 150 mV | 2.5 | 8 | V/ns |
| Rise/Fall Matching | T_{RFM} | Measured single-endedly from ± 75 mV | — | 20 | % |
| Voltage High | V_{HIGH} | | | 1.15 | V |
| Voltage Low | V_{LOW} | | -0.3 | — | V |

SL28EB742

Table 3. AC Electrical Specifications (Continued)

| Parameter | Symbol | Test Condition | Min | Max | Unit |
|--|----------------------|----------------------------------|----------|----------|------|
| Crossing Point Voltage at 0.7 V Swing | V_{OX} | | 300 | 550 | mV |
| PCI/PCIF at 3.3 V | | | | | |
| PCI Duty Cycle | T_{DC} | Measurement at 1.5 V | 45 | 55 | % |
| Spread Disabled PCIF/PCI Period | T_{PERIOD} | Measurement at 1.5 V | 29.99700 | 30.00300 | ns |
| Spread Enabled PCIF/PCI Period | $T_{PERIODSS}$ | Measurement at 1.5 V | 30.08421 | 30.23459 | ns |
| Spread Disabled PCIF/PCI Period | $T_{PERIODAbs}$ | Measurement at 1.5 V | 29.49700 | 30.50300 | ns |
| Spread Enabled PCIF/PCI Period | $T_{PERIODSSAbs}$ | Measurement at 1.5 V | 29.56617 | 30.58421 | ns |
| Spread Enabled PCIF and PCI High Time | T_{HIGH} | Measurement at 2 V | 12.27095 | 16.27995 | ns |
| Spread Enabled PCIF and PCI Low Time | T_{LOW} | Measurement at 0.8 V | 11.87095 | 16.07995 | ns |
| Spread Disabled PCIF and PCI High Time | T_{HIGH} | Measurement at 2.0 V | 12.27365 | 16.27665 | ns |
| Spread Disabled PCIF and PCI Low Time | T_{LOW} | Measurement at 0.8 V | 11.87365 | 16.07665 | ns |
| PCIF/PCI Rising/Falling Slew Rate | T_R / T_F | Measured between 0.8 V and 2.0 V | 1.0 | 4.0 | V/ns |
| Any PCI clock to Any PCI clock Skew | T_{SKEW} | Measurement at 1.5 V | — | 1000 | ps |
| PCIF and PCI Cycle to Cycle Jitter | T_{CCJ} | Measurement at 1.5 V | — | 300 | ps |
| PCIF/PCI Long Term Accuracy | L_{ACC} | Measurement at 1.5 V | — | 100 | ppm |
| 48M, 12_48M at 3.3 V | | | | | |
| Duty Cycle | T_{DC} | Measurement at 1.5 V | 45 | 55 | % |
| 48 MHz Period | T_{PERIOD} | Measurement at 1.5 V | 20.83125 | 20.83542 | ns |
| 48 MHz Absolute Period | $T_{PERIODAbs}$ | Measurement at 1.5 V | 20.48125 | 21.18542 | ns |
| 48 MHz High Time | T_{HIGH} | Measurement at 2 V | 8.216563 | 11.15198 | ns |
| 48 MHz Low Time | T_{LOW} | Measurement at 0.8 V | 7.816563 | 10.95198 | ns |
| Rising and Falling Edge Rate | T_R / T_F (48M) | Measured between 0.8 V and 2.0 V | 1.0 | 2.0 | V/ns |
| Rising and Falling Edge Rate | T_R / T_F (12_48M) | Measured between 0.8 V and 2.0 V | 1.0 | 2.0 | V/ns |
| Cycle to Cycle Jitter | T_{CCJ} | Measurement at 1.5 V | — | 300 | ps |

Table 3. AC Electrical Specifications (Continued)

| Parameter | Symbol | Test Condition | Min | Max | Unit |
|----------------------------------|---------------------------------|----------------------------------|----------|----------|------|
| 48M Long Term Accuracy | L _{ACC} | Measurement at 1.5 V | — | 100 | ppm |
| 25M at 3.3 V | | | | | |
| Duty Cycle | T _{DC} | Measurement at 1.5 V | 45 | 55 | % |
| Period | T _{PERIOD} | Measurement at 1.5 V | 39.996 | 40.004 | ns |
| Absolute Period | T _{PERIODAbs} | Measurement at 1.5 V | 39.32360 | 40.67640 | ns |
| Rising and Falling Edge Rate | T _R / T _F | Measured between 0.8 V and 2.0 V | 1.0 | 4.0 | V/ns |
| Cycle to Cycle Jitter | T _{CCJ} | Measurement at 1.5 V | — | 300 | ps |
| 25M Long Term Accuracy | L _{ACC} | Measured at 1.5 V | — | 100 | ppm |
| 14.318M, at 3.3 V | | | | | |
| Duty Cycle | T _{DC} | Measurement at 1.5 V | 45 | 55 | % |
| Period | T _{PERIOD} | Measurement at 1.5 V | 69.82033 | 69.86224 | ns |
| Absolute Period | T _{PERIODAbs} | Measurement at 1.5 V | 68.83429 | 70.84826 | ns |
| High Time | T _{HIGH} | Measurement at 2 V | 29.97543 | 38.46654 | ns |
| Low Time | T _{LOW} | Measurement at 0.8 V | 29.57543 | 38.26654 | ns |
| Rising and Falling Edge Rate | T _R / T _F | Measured between 0.8 V and 2.0 V | 1.0 | 4.0 | V/ns |
| Cycle to Cycle Jitter | T _{CCJ} | Measurement at 1.5 V | — | 500 | ps |
| Long Term Accuracy | L _{ACC} | Measurement at 1.5 V | — | 100 | ppm |
| ENABLE/DISABLE and SET-UP | | | | | |
| Clock Stabilization from Powerup | T _{STABLE} | | — | 1.8 | ms |
| Stop clock Set-up Time | T _{SS} | | 10.0 | — | ns |

Table 4. Thermal Conditions

| Parameter | Symbol | Condition | Min | Max | Unit |
|--|---------------|-----------------|-----|-----|------|
| Temperature, Storage | T_S | Non-functional | -65 | 150 | °C |
| Temperature, Operating Ambient, Extended | T_A | Functional | -40 | 85 | °C |
| Temperature, Operating Ambient, Commercial | T_A | Functional | 0 | 70 | °C |
| Temperature, Junction | T_J | Functional | — | 150 | °C |
| Dissipation, Junction to Case | θ_{JC} | JEDEC (JESD 51) | — | 20 | °C/W |
| Dissipation, Junction to Ambient | θ_{JA} | JEDEC (JESD 51) | — | 60 | °C/W |

Note: For multiple supplies, the voltage on any input or I/O pin cannot exceed the power pin during powerup. Power supply sequencing is not required.

Table 5. Absolute Maximum Conditions

| Parameter | Symbol | Test Condition | Min | Max | Unit |
|-----------------------------------|----------------|------------------------|------|-----|----------|
| Main Supply Voltage | $V_{DD_3.3V}$ | Functional | — | 4.6 | V |
| Input Voltage | V_{IN} | Relative to V_{SS} | -0.5 | 4.6 | V_{DC} |
| Temperature, Storage | T_S | Non-functional | -65 | 150 | °C |
| Temperature, Operating Ambient | T_A | Functional | -40 | 85 | °C |
| Temperature, Junction | T_J | Functional | — | 150 | °C |
| Dissipation, Junction to Case | θ_{JC} | JEDEC (JESD 51) | — | 20 | °C/W |
| Dissipation, Junction to Ambient | θ_{JA} | JEDEC (JESD 51) | — | 60 | °C/W |
| ESD Protection (Human Body Model) | ESD_{HBM} | JEDEC (JESD 22 - A114) | 2000 | — | V |
| Flammability Rating | UL-94 | UL (Class) | V-0 | | |
| Moisture Sensitivity Level | MSL | JEDEC (J-STD-020) | 1 | | |

Multiple Supplies: The Voltage on any input or I/O pin cannot exceed the power pin during power-up. Power supply sequencing is NOT required.

2. Functional Description

2.1. Powerdown (PD#) Clarification

The CKPWRGD/PD# pin is a dual-function pin. During initial powerup, the pin functions as CKPWRGD. Once CKPWRGD has been sampled high by the clock chip, the pin assumes PD# functionality. The PD# pin is an asynchronous active low input used to shut off all clocks cleanly before shutting off power to the device. This signal is synchronized internally to the device before powering down the clock synthesizer. PD# is also an asynchronous input for powering up the system. When PD# is asserted low, clocks are driven to a low value and held before turning off the VCOs and the crystal oscillator.

2.2. Powerdown (PD#) Assertion

When PD# is sampled low by two consecutive rising edges of CPU_C, all single-ended outputs clocks will be held low on their next high-to-low transition and differential clocks will be held low. When powerdown mode is desired as the initial power on state, PD# must be asserted low in less than 10 μ s after asserting CKPWRGD.

Table 6. Output Driver Status during CPU_STP# and PCIS_STP#

| | | CPU_STP# Asserted | PCI_STP# Asserted | CLKREQ# Asserted | SMBus OE Disabled |
|------------------------|---------------|------------------------------|------------------------------|-----------------------------|------------------------------|
| Single-ended Clocks | Stoppable | Running | Driven low | Running | Driven low |
| | Non-stoppable | Running | Running | Running | |
| Differential Clocks | Stoppable | Clock driven high | Clock driven high | Clock driven low | Clock driven low |
| | | Clock driven low | Clock driven low | Clock driven low | |
| | Non-stoppable | Running | Running | Running | |

Table 7. Output Driver Status

| | All Single-ended Clocks | | All Differential Clocks | |
|---------------------|--------------------------------|-----------------|--------------------------------|---------------|
| | w/o Strap | w/ Strap | Clock | Clock# |
| PD# = 0 (Powerdown) | Low | Hi-z | Low | Low |

2.3. Powerdown (PD#) Deassertion

The powerup latency is less than 1.8 ms. This is the time from the deassertion of the PD# pin or the ramping of the power supply until the time that stable clocks are generated from the clock chip. All differential outputs stopped in a three-state condition resulting from powerdown are driven high in less than 300 μ s of PD# deassertion to a voltage greater than 200 mV. After the clock chip's internal PLL is powered up and locked, all outputs are enabled within a few clock cycles. Figure 2 is an example showing the relationship of clocks coming up.




Figure 1. Powerdown Assertion Timing Waveform




Figure 2. Powerdown Deassertion Timing Waveform




Figure 3. CKPWRGD Timing Diagram

2.4. CPU_STP# Assertion

The CPU_STP# signal is an active LOW input used for synchronous stopping and starting the CPU output clocks while the rest of the clock generator continues to function. When the CPU_STP# pin is asserted, all CPU outputs that are set with the I²C configuration to be stoppable are stopped within two to six CPU clock periods after being sampled by two rising edges of the internal CPUC clock. The final states of the stopped CPU signals are CPUT = High and CPUC = Low.

2.5. CPU_STP# Deassertion

The deassertion of the CPU_STP# signal causes all stopped CPU outputs to resume normal operation in a synchronous manner. No short or stretched clock pulses are produced when the clock resumes. The maximum latency from the deassertion to active outputs is no more than two CPU clock cycles.




Figure 4. CPU_STP# Assertion Waveform




Figure 5. CPU_STP# Deassertion Waveform

2.6. PCI/SRC_STP# Assertion

The PCI/SRC_STP# signal is an active low input used for synchronously stopping and starting the PCI outputs while the rest of the clock generator continues to function. The set-up time for capturing PCI/SRC_STP# going low is 10 ns (t_{SU}) (refer to Figure 6). The PCIF and SRC clocks are affected by the PCI/SRC pin if their corresponding control bit in the I²C register is set to allow them to be free running. For SRC clocks assertion description, refer to the CPU_STP# descriptions in Section 2.4 and Section 2.5.




Figure 6. PCI/SRC_STP# Assertion Waveform

2.7. PCI/SRC_STP# Deassertion

The deassertion of the PCI/SRC_STP# signal causes all PCI and stoppable PCIF to resume running in a synchronous manner within two PCI clock periods and after PCI/SRC_STP# transitions to a high level. Similarly, PCI/SRC_STP# deassertion will cause stoppable SRC clocks to resume running. For an SRC clocks deassertion description, refer to the CPU_STP# description Section 2.4 and Section 2.5.




Figure 7. PCI/SRC_STP# Deassertion Waveform

3. Test and Measurement Setup

3.1. Single-ended Clocks

Figure 8 shows the test load configuration for single-ended clock output signals.




Figure 8. Single-ended Clocks Single Load Configuration




Figure 9. Single-ended Output Signals (for AC Parameters Measurement)

3.2. Differential Clock Signals

Figure 10 shows the test load configuration for differential clock signals.




Figure 10. 0.7 V Differential Load Configuration




Figure 11. Differential Measurement for Differential Output Signals
(for AC Parameters Measurement)




Figure 12. Single-ended Measurement for Differential Output Signals (for AC Parameters Measurement)

4. Control Registers

4.1. Frequency Select Pin FS

Apply the appropriate logic levels to FS inputs before CKPWRGD assertion to achieve host clock frequency selection. When the clock chip sampled HIGH on CKPWRGD and indicates that VTT voltage is stable then FS input values are sampled. This process employs a one-shot functionality and once the CKPWRGD sampled a valid HIGH, all other FS, and CKPWRGD transitions are ignored except in test mode.

Table 8. Frequency Select Pin (FS)

| SEL_SATA | FSC | FSB | FSA | CPU | SRC | SATA | PCI |
|----------|-----|-----|-----|--------|--------|--------|-------|
| 0 | 0 | 0 | 0 | 100.00 | 100.00 | 100.00 | 33.33 |
| 0 | 0 | 0 | 1 | 100.00 | 100.00 | 100.00 | 33.33 |
| 0 | 0 | 1 | 0 | 83.33 | 100.00 | 100.00 | 33.33 |
| 0 | 0 | 1 | 1 | 83.33 | 100.00 | 100.00 | 33.33 |
| 0 | 1 | 0 | 0 | 133.33 | 100.00 | 100.00 | 33.33 |
| 0 | 1 | 0 | 1 | 133.33 | 100.00 | 100.00 | 33.33 |
| 0 | 1 | 1 | 0 | 166.67 | 100.00 | 100.00 | 33.33 |
| 0 | 1 | 1 | 1 | 166.67 | 100.00 | 100.00 | 33.33 |
| 1 | 0 | 0 | 0 | 100.00 | 100.00 | 100.00 | 33.33 |
| 1 | 0 | 0 | 1 | 100.00 | 100.00 | 100.00 | 33.33 |
| 1 | 0 | 1 | 0 | 83.33 | 100.00 | 100.00 | 33.33 |
| 1 | 0 | 1 | 1 | 83.33 | 100.00 | 100.00 | 33.33 |
| 1 | 1 | 0 | 0 | 133.33 | 100.00 | 100.00 | 33.33 |
| 1 | 1 | 0 | 1 | 133.33 | 100.00 | 100.00 | 33.33 |
| 1 | 1 | 1 | 0 | 166.67 | 100.00 | 100.00 | 33.33 |
| 1 | 1 | 1 | 1 | 166.67 | 100.00 | 100.00 | 33.33 |

4.2. Serial Data Interface

To enhance the flexibility and function of the clock synthesizer, a two-signal serial interface is provided. Through the Serial Data Interface, various device functions, such as individual clock output buffers are individually enabled or disabled. The registers associated with the Serial Data Interface initialize to their default setting at power-up. The use of this interface is optional. Clock device register changes are normally made at system initialization, if any are required. The interface cannot be used during system operation for power management functions.

4.3. Data Protocol

The clock driver serial protocol accepts byte write, byte read, block write, and block read operations from the controller. For block write/read operation, access the bytes in sequential order from lowest to highest (most significant bit first) with the ability to stop after any complete byte is transferred. For byte write and byte read operations, the system controller can access individually indexed bytes. The offset of the indexed byte is encoded in the command code described in Table 9.

The block write and block read protocol is outlined in Table 10 while Table 11 outlines byte write and byte read protocol. The slave receiver address is 11010010 (D2h).

Table 9. Command Code Definition

| Bit | Description |
|-------|--|
| 7 | 0 = Block read or block write operation; 1 = Byte read or byte write operation. |
| (6:0) | Byte offset for byte read or byte write operation. For block read or block write operations, these bits should be '0000000'. |

Table 10. Block Read and Block Write Protocol

| Block Write Protocol | | Block Read Protocol | |
|----------------------|-------------------------------|---------------------|-------------------------------|
| Bit | Description | Bit | Description |
| 1 | Start | 1 | Start |
| 8:2 | Slave address–7 bits | 8:2 | Slave address–7 bits |
| 9 | Write | 9 | Write |
| 10 | Acknowledge from slave | 10 | Acknowledge from slave |
| 18:11 | Command Code–8 bits | 18:11 | Command Code–8 bits |
| 19 | Acknowledge from slave | 19 | Acknowledge from slave |
| 27:20 | Byte Count–8 bits | 20 | Repeat start |
| 28 | Acknowledge from slave | 27:21 | Slave address–7 bits |
| 36:29 | Data byte 1–8 bits | 28 | Read = 1 |
| 37 | Acknowledge from slave | 29 | Acknowledge from slave |
| 45:38 | Data byte 2–8 bits | 37:30 | Byte Count from slave–8 bits |
| 46 | Acknowledge from slave | 38 | Acknowledge |
| | Data Byte /Slave Acknowledges | 46:39 | Data byte 1 from slave–8 bits |

Table 10. Block Read and Block Write Protocol (Continued)

| Block Write Protocol | | Block Read Protocol | |
|----------------------|------------------------|---------------------|-------------------------------------|
| Bit | Description | Bit | Description |
| | Data Byte N–8 bits | 47 | Acknowledge |
| | Acknowledge from slave | 55:48 | Data byte 2 from slave–8 bits |
| | Stop | 56 | Acknowledge |
| | | | Data bytes from slave / Acknowledge |
| | | | Data Byte N from slave–8 bits |
| | | | NOT Acknowledge |
| | | | Stop |

Table 11. Byte Read and Byte Write Protocol

| Byte Write Protocol | | Byte Read Protocol | |
|---------------------|------------------------|--------------------|------------------------|
| Bit | Description | Bit | Description |
| 1 | Start | 1 | Start |
| 8:2 | Slave address–7 bits | 8:2 | Slave address–7 bits |
| 9 | Write | 9 | Write |
| 10 | Acknowledge from slave | 10 | Acknowledge from slave |
| 18:11 | Command Code–8 bits | 18:11 | Command Code–8 bits |
| 19 | Acknowledge from slave | 19 | Acknowledge from slave |
| 27:20 | Data byte–8 bits | 20 | Repeated start |
| 28 | Acknowledge from slave | 27:21 | Slave address–7 bits |
| 29 | Stop | 28 | Read |
| | | 29 | Acknowledge from slave |
| | | 37:30 | Data from slave–8 bits |
| | | 38 | NOT Acknowledge |
| | | 39 | Stop |

SL28EB742

Control Register 0. Byte 0

| Bit | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 |
|------|-----|-----|---------------|----------|-----|-----|-----|-----|
| Name | | | Spread Enable | SEL_SATA | | FSC | FSB | FSA |
| Type | R/W | R/W | R/W | R | R/W | R | R | R |

Reset settings = 000x0xxx

| Bit | Name | Function |
|-----|---------------|---|
| 7:6 | Reserved | |
| 5 | Spread Enable | Enable spread for CPU/SRC/PCI outputs 0 = Disable, 1 = -0.5% |
| 4 | SEL_SATA | See Table 9 for SATA/SRC selection. |
| 3 | Reserved | |
| 2 | FSC | See Table 9 for CPU Frequency Selection Table. |
| 1 | FSB | |
| 0 | FSA | |

Register 1. Byte 1

| Bit | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 |
|------|----------|--------------|--------------|------|------|-----|--------|-----|
| Name | DOT96_OE | SATA/SRC0_OE | CPU2/SRC6_OE | SRC2 | SRC1 | | WOL_EN | |
| Type | R/W | R/W | R/W | R/W | R/W | R/W | R/W | R/W |

Reset settings = 1111110

| Bit | Name | Function |
|-----|--------------|---|
| 7 | DOT96_OE | Output enable for DOT96. 0 = Output Disabled, 1 = Output Enabled |
| 6 | SATA/SRC0_OE | Output enable for SATA/SRC0. 0 = Output Disabled, 1 = Output Enabled |
| 5 | CPU2/SRC6_OE | Output enable for CPU2/SRC6. 0 = Output Disabled, 1 = Output Enabled |
| 4 | SRC2 | Output enable for SRC2. 0 = Output Disabled, 1 = Output Enabled |
| 3 | SRC1 | Output enable for SRC1. 0 = Output Disabled, 1 = Output Enabled |
| 2 | Reserved | |
| 1 | WOL_EN | Wake-On-LAN Enable bit. 25 MHz free running during VDD Suspend (S-states). If this bit is set to 0, the XTAL OSC will also be powered down in the Suspend States) |
| 0 | Reserved | |

SL28EB742

Register 2. Byte 2

| Bit | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 |
|------|--------|-----|--------|--------|-----------|---------|---------|-----|
| Name | 48M_OE | | 25M_OE | REF_OE | 12_48M_OE | PCI0_OE | PCIF_OE | |
| Type | R/W | R/W | R/W | R/W | R/W | R/W | R/W | R/W |

Reset settings = 10111110

| Bit | Name | Function |
|-----|-----------|---|
| 7 | 48M_OE | Output Enable for 48M. 0: Output disabled. 1: Output enabled. |
| 6 | Reserved | |
| 5 | 25M_OE | Output ENABLE for 25M. 0 = Output Disabled, 1 = Output Enabled |
| 4 | REF_OE | Output Enable for REF. 0 = Output Disabled, 1 = Output Enabled |
| 3 | 12_48M_OE | Output Enable for 12_48M. 0 = Output Disabled, 1 = Output Enabled |
| 2 | PCI0_OE | Output Enable for PCI0. 0 = Output Disabled, 1 = Output Enabled |
| 1 | PCIF_OE | Output Enable for PCIF. 0 = Output Disabled, 1 = Output Enabled |
| 0 | Reserved | |

Register 3. Byte 3

| Bit | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 |
|------|---------|---------|-----------|-----------|-----------|-----------|-----------|-----------|
| Name | CPU1_OE | CPU0_OE | CLKREQ#_3 | CLKREQ#_3 | CLKREQ#_2 | CLKREQ#_2 | CLKREQ#_1 | CLKREQ#_1 |
| Type | R/W | R/W | R/W | R/W | R/W | R/W | R/W | R/W |

Reset settings = 1100000

| Bit | Name | Function |
|-----|-----------|--|
| 7 | CPU1_OE | Output Enable for CPU1. 0 = Output Disabled, 1 = Output Enabled |
| 6 | CPU0_OE | Output Enable for CPU0. 0 = Output Disabled, 1 = Output Enabled |
| 5 | CLKREQ#_3 | Clock Request for SRC2. 0 = Not controlled, 1 = Controlled |
| 4 | CLKREQ#_3 | Clock Request for SRC6 (does not apply to CPU clock). 0 = Not controlled, 1 = Controlled |
| 3 | CLKREQ#_2 | Clock Request for SRC2. 0 = Not controlled, 1 = Controlled |
| 2 | CLKREQ#_2 | Clock Request for SATA75M/SRC0. 0 = Not controlled, 1 = Controlled |
| 1 | CLKREQ#_1 | Clock Request for SRC1. 0 = Not controlled, 1 = Controlled |
| 0 | CLKREQ#_1 | Clock Request for SATA75M/SRC0. 0 = Not controlled, 1 = Controlled |

SL28EB742

Register 4. Byte 4

| Bit | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 |
|------|-----|------|--------|------|--------|-----|------|-----|
| Name | | CPU1 | 12_48M | CPU2 | ITP_EN | | CPU0 | |
| Type | R/W | R/W | R | R/W | R | R/W | R/W | R/W |

Reset settings = 00x0x000

| Bit | Name | Function |
|-----|----------|--|
| 7 | Reserved | |
| 6 | CPU1 | CPU1 Free Run Control. 0 = Free Running, 1 = Stoppable |
| 5 | 12_48M | Selectable 12_48M Status. 0 = 48M, 1 = 12M |
| 4 | CPU2 | CPU2 Free Run Control. 0 = Free Running, 1 = Stoppable |
| 3 | ITP_EN | Selectable CPUe_ITP/ SRC6 Status. 0 = SRC6, 1 = CPU2 |
| 2 | Reserved | |
| 1 | CPU0 | CPU0 Free Run Control. 0 = Free Running, 1 = Stoppable |
| 0 | Reserved | |

Control Register 5. Byte 5

| Bit | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 |
|-------------|-------------|-----|-----|------|------|------|-----|-----|
| Name | SATA75/SRC0 | | | SRC6 | SRC2 | SRC1 | | |
| Type | R/W | R/W | R/W | R/W | R/W | R/W | R/W | R/W |

Reset settings = 00010000

| Bit | Name | Function |
|-----|-------------|---|
| 7:5 | Reserved | |
| 4 | SATA75/SRC0 | SATA75/SRC0 Free Run Control. 0 = Free Running, 1 = Stoppable |
| 3 | SRC6 | SRC6 Free Run Control. 0 = Free Running, 1 = Stoppable |
| 2 | SRC2 | SRC2 Free Run Control. 0 = Free Running, 1 = Stoppable |
| 1 | SRC1 | SRC1 Free Run Control. 0 = Free Running, 1 = Stoppable |
| 0 | Reserved | |

Control Register 6. Byte 6

| Bit | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 |
|-------------|---------|-----|---------|-----|-----------|-----|----------|-----|
| Name | CPU_AMP | | SRC_AMP | | DOT96_AMP | | SATA_AMP | |
| Type | R/W | R/W | R/W | R/W | R/W | R/W | R/W | R/W |

Reset settings = 01010101

| Bit | Name | Function |
|-----|-----------|---|
| 7:6 | CPU_AMP | CPU Amplitude Adjustment. 00 = 700 mV, 01 = 800 mV, 10 = 900 mV, 11 = 1000 mV |
| 5:4 | SRC_AMP | SRC Amplitude Adjustment. 00 = 700 mV, 01 = 800 mV, 10 = 900 mV, 11 = 1000 mV |
| 3:2 | DOT96_AMP | DOT96 Amplitude Adjustment. 00 = 700 mV, 01 = 800 mV, 10 = 900 mV, 11 = 1000 mV |
| 1:0 | SATA_AMP | SATA75/SRC0 Amplitude Adjustment. 00 = 700 mV, 01 = 800 mV, 10 = 900 mV, 11 = 1000 mV |

SL28EB742

Control Register 7. Byte 7

| Bit | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 |
|------|----------------|----------------|----------------|----------------|-----------------|-----------------|-----------------|-----------------|
| Name | Rev Code Bit 3 | Rev Code Bit 2 | Rev Code Bit 1 | Rev Code Bit 0 | Vendor ID Bit 3 | Vendor ID Bit 2 | Vendor ID Bit 1 | Vendor ID Bit 0 |
| Type | R | R | R | R | R | R | R | R |

Reset settings = 00011000

| Bit | Name | Function |
|-----|-----------------|---------------------|
| 7 | Rev Code Bit 3 | Revision Code Bit 3 |
| 6 | Rev Code Bit 2 | Revision Code Bit 2 |
| 5 | Rev Code Bit 1 | Revision Code Bit 1 |
| 4 | Rev Code Bit 0 | Revision Code Bit 0 |
| 3 | Vendor ID Bit 3 | Vendor ID Bit 3 |
| 2 | Vendor ID Bit 2 | Vendor ID Bit 2 |
| 1 | Vendor ID Bit 1 | Vendor ID Bit 1 |
| 0 | Vendor ID Bit 0 | Vendor ID Bit 0 |

Control Register 8. Byte 8

| Bit | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 |
|-------------|-----|-----|-----|-----|-----|-----|-----|-----|
| Name | BC7 | BC6 | BC5 | BC4 | BC3 | BC2 | BC1 | BC0 |
| Type | R/W | R/W | R/W | R/W | R/W | R/W | R/W | R/W |

Reset settings = 00001111

| Bit | Name | Function |
|-----|------|--|
| 7 | BC7 | Byte count register for block read operation. The default value for Byte count is 15. In order to read beyond Byte 15, the user should change the byte count limit to or beyond the byte that is desired to be read. |
| 6 | BC6 | |
| 5 | BC5 | |
| 4 | BC4 | |
| 3 | BC3 | |
| 2 | BC2 | |
| 1 | BC1 | |
| 0 | BC0 | |

SL28EB742

Control Register 9. Byte 9

| Bit | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 |
|------|------|------|------|------|------|------|------|------|
| Name | SRC5 | SRC4 | SRC3 | SRC5 | SRC4 | SRC3 | PCI0 | PCIF |
| Type | R/W | R/W | R/W | R/W | R/W | R/W | R/W | R/W |

Reset settings = 11100001

| Bit | Name | Function |
|-----|------|---|
| 7 | SRC5 | Output Enable for SRC5. 0 = Output Disabled, 1 = Output Enabled |
| 6 | SRC4 | Output Enable for SRC4. 0 = Output Disabled, 1 = Output Enabled |
| 5 | SRC3 | Output Enable for SRC3. 0 = Output Disabled, 1 = Output Enabled |
| 4 | SRC5 | SRC5 Free Run Control. 0 = Free Running, 1 = Stoppable |
| 3 | SRC4 | SRC4 Free Run Control. 0 = Free Running, 1 = Stoppable |
| 2 | SRC3 | SRC3 Free Run Control. 0 = Free Running, 1 = Stoppable |
| 1 | PCI0 | PCI0 Free Run Control. 0 = Free Running, 1 = Stoppable |
| 0 | PCIF | PCIF Free Run Control. 0 = Free Running, 1 = Stoppable |

Control Register 10. Byte 10

| Bit | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 |
|-------------|-----|-----|-----|-----|-----|-----|-----|-----|
| Name | | | | | | | | |
| Type | R/W | R/W | R/W | R/W | R/W | R/W | R/W | R/W |

Reset settings = 00000000

| Bit | Name | Function |
|-----|----------|----------|
| 7:0 | Reserved | |

Control Register 11. Byte 11

| Bit | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 |
|-------------|----------|----------|----------|----------|----------|----------|-------------|-------------|
| Name | 14M_Bit2 | 14M_Bit1 | 14M_Bit0 | 25M_Bit2 | 25M_Bit1 | 25M_Bit0 | 12_48M_Bit2 | 12_48M_Bit0 |
| Type | R/W | R/W | R/W | R/W | R/W | R/W | R/W | R/W |

Reset settings = 10110111

| Bit | Name | Function | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|-------------------|-------------|--|------|------|---|------|-----------------|--|---|---|---|---|--|---|---|---|--|---|---|---|--|---|---|---|--|---|---|---|---------|---|---|---|--|---|---|---|-------------------|---|---|---|
| 7 | 14M_Bit2 | Drive Strength Control - Bit[2:0] Normal mode default '101' Wireless Friendly Mode default to '111' | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6 | 14M_Bit1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5 | 14M_Bit0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | 25M_Bit2 | <table border="1"> <thead> <tr> <th>Mode</th> <th>Bit2</th> <th>Bit1</th> <th>Bit0</th> <th>Buffer Strength</th> </tr> </thead> <tbody> <tr> <td></td> <td>0</td> <td>0</td> <td>0</td> <td rowspan="7"> <div style="text-align: center;"> <p>Strong</p> <p>↓</p> <p>Weak</p> </div> </td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>1</td> </tr> <tr> <td></td> <td>0</td> <td>1</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td>1</td> <td>1</td> </tr> <tr> <td></td> <td>1</td> <td>0</td> <td>0</td> </tr> <tr> <td>Default</td> <td>1</td> <td>0</td> <td>1</td> </tr> <tr> <td></td> <td>1</td> <td>1</td> <td>0</td> </tr> <tr> <td>Wireless Friendly</td> <td>1</td> <td>1</td> <td>1</td> </tr> </tbody> </table> | Mode | Bit2 | Bit1 | Bit0 | Buffer Strength | | 0 | 0 | 0 | <div style="text-align: center;"> <p>Strong</p> <p>↓</p> <p>Weak</p> </div> | | 0 | 0 | 1 | | 0 | 1 | 0 | | 0 | 1 | 1 | | 1 | 0 | 0 | Default | 1 | 0 | 1 | | 1 | 1 | 0 | Wireless Friendly | 1 | 1 | 1 |
| Mode | Bit2 | | Bit1 | Bit0 | Buffer Strength | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 0 | | 0 | 0 | <div style="text-align: center;"> <p>Strong</p> <p>↓</p> <p>Weak</p> </div> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 0 | | 0 | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 0 | | 1 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 0 | | 1 | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 1 | | 0 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Default | 1 | 0 | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 1 | 1 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Wireless Friendly | 1 | 1 | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | 25M_Bit1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | 25M_Bit0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 12_48M_Bit2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0 | 12_48M_Bit0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

SL28EB742

Control Register 12. Byte 12

| Bit | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 |
|-------------|----------|----------|----------|-----------|-----------|-----------|-----|-------------|
| Name | 48M_Bit2 | 48M_Bit1 | 48M_Bit0 | PCI0_Bit2 | PCI0_Bit1 | PCI0_Bit0 | | 12_48M_Bit1 |
| Type | R/W | R/W | R/W | R/W | R/W | R/W | R/W | R/W |

Reset settings = 10110100

| Bit | Name | Function | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|----------------|-------------|---|----------|----------|---------------------|------|-----------------|--|---|---|---|---------------------|--|---|---|---|--|---|---|---|--|---|---|---|--|---|---|---|----------------|----------|----------|----------|--|---|---|---|---|-------------|-------------------|---|---|---|
| 7 | 48M_Bit2 | Drive Strength Control - Bit[2:0] Normal mode default '101' Wireless Friendly Mode default to '111' <table border="1" style="margin-left: 20px;"> <thead> <tr> <th>Mode</th> <th>Bit2</th> <th>Bit1</th> <th>Bit0</th> <th>Buffer Strength</th> </tr> </thead> <tbody> <tr> <td></td> <td>0</td> <td>0</td> <td>0</td> <td rowspan="7" style="text-align: center;"> Strong ↓ Weak </td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>1</td> </tr> <tr> <td></td> <td>0</td> <td>1</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td>1</td> <td>1</td> </tr> <tr> <td></td> <td>1</td> <td>0</td> <td>0</td> </tr> <tr style="background-color: yellow;"> <td>Default</td> <td>1</td> <td>0</td> <td>1</td> </tr> <tr> <td></td> <td>1</td> <td>1</td> <td>0</td> </tr> <tr> <td>0</td> <td>12_48M_Bit1</td> <td>Wireless Friendly</td> <td>1</td> <td>1</td> <td>1</td> </tr> </tbody> </table> | Mode | Bit2 | Bit1 | Bit0 | Buffer Strength | | 0 | 0 | 0 | Strong ↓ Weak | | 0 | 0 | 1 | | 0 | 1 | 0 | | 0 | 1 | 1 | | 1 | 0 | 0 | Default | 1 | 0 | 1 | | 1 | 1 | 0 | 0 | 12_48M_Bit1 | Wireless Friendly | 1 | 1 | 1 |
| Mode | Bit2 | | Bit1 | Bit0 | Buffer Strength | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 0 | | 0 | 0 | Strong ↓ Weak | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 0 | | 0 | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 0 | | 1 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 0 | | 1 | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 1 | | 0 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Default | 1 | | 0 | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 1 | 1 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0 | 12_48M_Bit1 | Wireless Friendly | 1 | 1 | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6 | 48M_Bit1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5 | 48M_Bit0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | PCI0_Bit2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | PCI0_Bit1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | PCI0_Bit0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | Reserved | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0 | 12_48M_Bit1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Control Register 13. Byte 13

| Bit | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 |
|-------------|-----------|-----------|-----------|-----|-----|-----|-----|------------------------|
| Name | PCIF_Bit2 | PCIF_Bit1 | PCIF_Bit0 | | | | | Wireless Friendly Mode |
| Type | R/W | R/W | R/W | R/W | R/W | R/W | R/W | R/W |

Reset settings = 10100000

| Bit | Name | Function | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|------------------------|---|------|---------------------|------|------|-----------------|--|---|---|---|---------------------|--|---|---|---|--|---|---|---|--|---|---|---|--|---|---|---|---------|---|---|---|--|---|---|---|-------------------|---|---|---|
| 7 | PCIF_Bit2 | Drive Strength Control—Bit[2:0] Normal mode default 101 Wireless Friendly Mode default to '111' | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6 | PCIF_Bit1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5 | PCIF_Bit0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"> <thead> <tr> <th>Mode</th> <th>Bit2</th> <th>Bit1</th> <th>Bit0</th> <th>Buffer Strength</th> </tr> </thead> <tbody> <tr> <td></td> <td>0</td> <td>0</td> <td>0</td> <td rowspan="8" style="text-align: center;"> Strong ↓ Weak </td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>1</td> </tr> <tr> <td></td> <td>0</td> <td>1</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td>1</td> <td>1</td> </tr> <tr> <td></td> <td>1</td> <td>0</td> <td>0</td> </tr> <tr> <td>Default</td> <td>1</td> <td>0</td> <td>1</td> </tr> <tr> <td></td> <td>1</td> <td>1</td> <td>0</td> </tr> <tr> <td>Wireless Friendly</td> <td>1</td> <td>1</td> <td>1</td> </tr> </tbody> </table> | | | Mode | Bit2 | Bit1 | Bit0 | Buffer Strength | | 0 | 0 | 0 | Strong ↓ Weak | | 0 | 0 | 1 | | 0 | 1 | 0 | | 0 | 1 | 1 | | 1 | 0 | 0 | Default | 1 | 0 | 1 | | 1 | 1 | 0 | Wireless Friendly | 1 | 1 | 1 |
| Mode | Bit2 | Bit1 | Bit0 | Buffer Strength | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 0 | 0 | 0 | Strong ↓ Weak | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 0 | 0 | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 0 | 1 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 0 | 1 | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 1 | 0 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Default | 1 | 0 | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 1 | 1 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Wireless Friendly | 1 | 1 | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4:1 | Reserved | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0 | Wireless Friendly Mode | Wireless Friendly Mode. 0 = Disabled, Default all single-ended clocks slew rate config bits to 101 1 = Enabled, Default all single-ended clocks slew rate config bits to 111 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

SL28EB742

Control Register 14. Byte 14

| Bit | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 |
|------|-----|-----|-----|-------|-------|-------|-------|-------|
| Name | | | | OTP_4 | OTP_3 | OTP_2 | OTP_1 | OTP_0 |
| Type | R/W | R/W | R/W | R/W | R/W | R/W | R/W | R/W |

Reset settings = 10101000

| Bit | Name | Function |
|-----|----------|--|
| 7:5 | Reserved | |
| 4 | OTP_4 | OTP_ID. Identification for programmed device |
| 3 | OTP_3 | |
| 2 | OTP_2 | |
| 1 | OTP_1 | |
| 0 | OTP_0 | |

5. Pin Descriptions: 56-Pin QFN




Table 12. 56-QFN Pin Definitions

| Pin # | Name | Type | Description |
|-------|-------------------|-------------|---|
| 1 | PCIF/ITP_EN** | I/O, SE, PD | 33 MHz free running clock output/3.3 V LVTTTL input to enable SRC6 or CPU2_ITP (sampled on the CKPWRGD assertion). 0 = SRC6, 1 = CPU2 |
| 2 | CLKREQ#3** | I, PD | 3.3 V clock request input (internal 100 kΩ pull-down) |
| 3 | 12_48M / SEL12_48 | I/O, SE PU | 12/48 MHz Clock output/3.3 V-tolerance input for 12 MHz or 48 MHz selection (Sampled at CKPWRGD assertion) (internal 100 kΩ pull-up). 0 = 48M, 1 = 12M |
| 4 | VDD_48 | PWR | 3.3 V Power supply |
| 5 | 48M/FSA** | I/O PD | Fixed 48 MHz clock output/3.3 V-tolerant input for CPU frequency selection (internal 100 kΩ pull-down). Refer to Table 2 for Vil_FS and Vih_FS specifications. |
| 6 | GND_48 | GND | Ground. |
| 7 | GND_48 | GND | Ground. |
| 8 | DOT96 | O, DIF | Fixed true 96 MHz clock output. |
| 9 | DOT96# | O, DIF | Fixed complement 96 MHz clock output. |
| 10 | FSB** | I, PD | 3.3 V-tolerant input for CPU frequency selection (internal 100 kΩ pull-down). Refer to Table 2 for Vil_FS and Vih_FS specifications. |
| 11 | GND_SATA | GND | Ground. |
| 12 | SATA/SRC0 | O, DIF | 100 MHz True differential serial reference clock. |
| 13 | SATA/SRC0# | O, DIF | 100 MHz Complement differential serial reference clock. |
| 14 | VDD_SATA | PWR | 3.3 V Power supply. |
| 15 | SRC1 | O, DIF | 100 MHz True differential serial reference clock. |
| 16 | SRC1# | O, DIF | 100 MHz Complement differential serial reference clock. |
| 17 | SRC2 | O, DIF | 100 MHz True differential serial reference clock. |
| 18 | SRC2# | O, DIF | 100 MHz Complement differential serial reference clock. |
| 19 | SRC3 | O, DIF | 100 MHz True differential serial reference clock. |
| 20 | SRC3# | O, DIF | 100 MHz Complement differential serial reference clock. |
| 21 | GND_SRC | GND | Ground. |
| 22 | VDD_SRC | PWR | 3.3 V Power supply. |
| 23 | SRC4# | O, DIF | 100 MHz True differential serial reference clock. |
| 24 | SRC4 | O, DIF | 100 MHz Complement differential serial reference clock. |
| 25 | SRC5# | O, DIF | 100 MHz True differential serial reference clock. |

Table 12. 56-QFN Pin Definitions (Continued)

| Pin # | Name | Type | Description |
|-------|-----------------|--------|--|
| 26 | SRC5 | O, DIF | 100 MHz Complement differential serial reference clock. |
| 27 | GND_SRC | GND | Ground. |
| 28 | VDD_SRC | PWR | 3.3 V Power supply. |
| 29 | SRC6#/CPU2_ITP# | O, DIF | Selectable complementary differential CPU or SRC clock output. ITP_EN = 0 @ CKPWRGD assertion = SRC6 ITP_EN = 1 @ CKPWRGD assertion = CPU2 |
| 30 | SRC6/CPU2_ITP | O, DIF | Selectable True differential CPU or SRC clock output. ITP_EN = 0 @ CKPWRGD assertion = SRC6 ITP_EN = 1 @ CKPWRGD assertion = CPU2 |
| 31 | CPU1# | O, DIF | Complement differential CPU clock output. |
| 32 | CPU1 | O, DIF | True differential CPU clock output. |
| 33 | VDD_CPU | PWR | 3.3 V Power supply. |
| 34 | CPU0# | O, DIF | Complement differential CPU clock output. |
| 35 | CPU0 | O, DIF | True differential CPU clock output. |
| 36 | GND_CPU | GND | Ground |
| 37 | SCLK | I | SMBus compatible SCLOCK. |
| 38 | SDATA | I/O | SMBus compatible SDATA. |
| 39 | CPU_STP#* | I, PU | 3.3 V-tolerant input for stopping CPU outputs (internal 100 kΩ pull-up). |
| 40 | PCI/SRC_STP#* | I, PU | 3.3 V-tolerant input for stopping PCI and SRC outputs (internal 100 kΩ pull-up). |
| 41 | XOUT | O | 14.318 MHz Crystal output. Float XOUT if using only CLKIN (Clock input). |
| 42 | XIN/CLKIN | I | 14.318 MHz Crystal input or 3.3 V, 14.318 MHz Clock Input |
| 43 | GND_REF | GND | Ground for REF clock and WOL support. |
| 44 | GND_REF | GND | Ground for REF clock and WOL support. |
| 45 | REF | O | 14.318 MHz reference output clock. |
| 46 | VDD_REF | PWR | 3.3 V Power Supply for REF clock and power to support WOL. |
| 47 | VDD_REF | PWR | 3.3 V Power Supply for REF clock and power to support WOL. |
| 48 | CKPWRGD/PD# | I | 3.3 V LVTTTL input. This pin is a level sensitive strobe used to determine when latch inputs are valid and are ready to be sampled. |
| 49 | VDD_25 | PWR | 3.3 V Power supply. |

Table 12. 56-QFN Pin Definitions (Continued)

| Pin # | Name | Type | Description |
|-------|-----------------|---------------|---|
| 50 | 25M/FSC** | I/O, PD | Fixed 25 MHz clock output/3.3 V-tolerant input for CPU frequency selection (internal 100 k Ω pull-up). Refer to DC Electrical Specifications table for V_{iL_FS} and V_{iH_FS} specifications. |
| 51 | GND_25 | GND | Ground. |
| 52 | CLKREQ#1** | I, PD | 3.3 V clock request input (internal 100 k Ω pull-down) |
| 53 | CLKREQ#2** | I, PD | 3.3 V clock request input (internal 100 k Ω pull-down) |
| 54 | PCI0/SEL_SATA** | I/O, SE PD | 33 MHz clock output/3.3 V LVTTTL input to enable 100 MHz SATA (internal 100 k Ω pull-up). 0 = SATA/SRC0 = SRC0 1 = SATA/SRC0 = SATA |
| 55 | GND_PCI | GND | Ground. |
| 56 | VDD_PCI | PWR | 3.3 V Power supply. |

6. Ordering Guide

| Part Number | Package Type | Product Flow |
|--------------------|--------------------------|--------------------------|
| Lead-free | | |
| SL28EB742ALC | 56-pin QFN | Industrial, 0 to 70 °C |
| SL28EB742ALCT | 56-pin QFN Tape and Reel | Industrial, 0 to 70 °C |
| SL28EB742ALI | 56-pin QFN | Industrial, -40 to 85 °C |
| SL28EB742ALIT | 56-pin QFN Tape and Reel | Industrial, -40 to 85 °C |

7. Package Outline

Figure 13 illustrates the package details for the SL28EB742. Table 13 lists the values for the dimensions shown in the illustration.




Figure 13. 56-Lead QFN Package

Table 13. Package Diagram Dimensions

| Symbol | Millimeters | | |
|--|-------------|------|------|
| | Min | Nom | Max |
| A | 0.70 | 0.75 | 0.80 |
| A1 | 0.00 | 0.02 | 0.05 |
| A3 | 0.20 REF | | |
| b | 0.18 | 0.25 | 0.30 |
| D | 8.00 BSC | | |
| D2 | 5.80 | 5.90 | 6.00 |
| e | 0.50 BSC | | |
| E | 8.00 BSC | | |
| E2 | 5.80 | 5.90 | 6.00 |
| L | 0.30 | 0.40 | 0.50 |
| aaa | 0.10 | | |
| bbb | 0.10 | | |
| ccc | 0.10 | | |
| ddd | 0.10 | | |
| eee | 0.08 | | |
| Notes: | | | |
| 1. All dimensions shown are in millimeters (mm) unless otherwise noted. | | | |
| 2. Dimensioning and Tolerancing per ANSI Y14.5M-1994. | | | |
| 3. Recommended card reflow profile is per the JEDEC/IPC J-STD-020 specification for Small Body Components. | | | |
| 4. This drawing conforms to the JEDEC Solid State Outline MO-220. | | | |

DOCUMENT CHANGE LIST

Revision 0.1 to Revision 0.2

- Correct the pin description.
- Remove 75 MHz description on pin description.
- Remove WOL function description
- Correct OTP code to 01000

CONTACT INFORMATION

Silicon Laboratories Inc.

400 West Cesar Chavez
Austin, TX 78701
Tel: 1+(512) 416-8500
Fax: 1+(512) 416-9669
Toll Free: 1+(877) 444-3032

Please visit the Silicon Labs Technical Support web page:

<https://www.silabs.com/support/pages/contacttechnicalsupport.aspx>

and register to submit a technical support request.

The information in this document is believed to be accurate in all respects at the time of publication but is subject to change without notice. Silicon Laboratories assumes no responsibility for errors and omissions, and disclaims responsibility for any consequences resulting from the use of information included herein. Additionally, Silicon Laboratories assumes no responsibility for the functioning of undescribed features or parameters. Silicon Laboratories reserves the right to make changes without further notice. Silicon Laboratories makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Silicon Laboratories assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Silicon Laboratories products are not designed, intended, or authorized for use in applications intended to support or sustain life, or for any other application in which the failure of the Silicon Laboratories product could create a situation where personal injury or death may occur. Should Buyer purchase or use Silicon Laboratories products for any such unintended or unauthorized application, Buyer shall indemnify and hold Silicon Laboratories harmless against all claims and damages.

Silicon Laboratories and Silicon Labs are trademarks of Silicon Laboratories Inc.

Other products or brandnames mentioned herein are trademarks or registered trademarks of their respective holders.